

PowerLite[®] **83c**
Multimedia Projector



Epson[®] — the world's
leading projectors



Key Features

- Brilliant, sharp and engaging multimedia presentations with 2200 lumens and native XGA resolution
- Convenient closed captioning included, with no additional hardware required*
- Amazing audio that's sure to fill any classroom with built-in 7 W speaker
- RJ-45 connectivity and included software to monitor the projector over a network
- Great positioning flexibility with 1.2x zoom ratio
- More intense, sharper images, with the latest generation of high aperture, Epson 3LCD technology
- Direct power on/off for remote free power control on installed units
- Energy-efficient E-TORL™ lamp technology — delivers more lumens per watt, lasts up to 4000 hours for added cost savings
- Easy lamp and air filter access for quick, convenient replacements
- Convenient anchor bar for added security in any environment

Key Dates

Product Ship	April 2, 2007
Announcement	April 2, 2007
Dates subject to change	

Ordering Information

Product Name	Product Code	UPC
PowerLite 83c	V11H255020	0 10343 86408 5
Replacement lamp	V13H010L42	0 10343 86411 5
Replacement air filter	V13H134A13	0 10343 86412 2

* Initial units shipped may require firmware download

Epson PowerLite 83c Specifications

Projection System

High aperture Epson 3LCD technology

Projection Method

Front/rear/ceiling mount

LCD

Driving Method

Epson Poly-silicon TFT Active Matrix

Pixel Number

786,432 dots (1024 x 768) x 3 LCDs

Native Resolution

XGA

Aspect Ratio

4:3 (supports 16:9)

Pixel Arrangement

Cross stripe

Projection Lens

F-number

1.6 – 1.74

Focal Length

18.4 – 22.12 mm

Zoom Ratio

Optical zoom 1.0 – 1.2

Lamp

Type

E-TORL 170 W UHE

Life*

3000 hours (High Brightness Mode)

4000 hours (Low Brightness Mode)

Screen

Screen Width Ratio (distance/width)

1.46 – 2:0

Screen Size (projected distance)

30" – 300" (2.7' – 34.2')

Keystone Correction

Automatic, vertical: ± 30 degrees

Brightness (High Brightness Mode)

Up to 2200 lumens

Contrast Ratio (High Brightness, Game Mode)

Up to 400:1

Brightness Uniformity (typical)

90%

Color Reproduction

16.7 million colors

Audio Output

7 W monaural

Operating Temperature

41° to 95° F (5° to 35° C)

Power Supply Voltage

100 – 240 V $\pm 10\%$, 50/60 Hz AC

Power Consumption

248 W, 5 W standby network on, 4.1 W network off

Dimensions (W x D x H)

Including feet
9.6" x 12.9" x 4.3"

Excluding feet

9.6" x 12.9" x 3.6"

Weight

6.4 lb/2.9 kg

Fan Noise

35 dB (High Brightness Mode)

28 dB (Low Brightness Mode)

Effective Scanning Frequency Range

Pixel clock

13.5 MHz – 162 MHz

Horizontal

15 KHz – 92 KHz

Vertical

50 Hz – 85 Hz

Remote Control

Features

Source search, power, aspect, color mode, volume, e-zoom, A/V mute, freeze, menu, help, auto

Operating Angle

Right/left ± 30 degrees

Upper/lower ± 15 degrees

Operating Distance

19.7 ft (6 m)

Display performance

Native

1024 x 768

Resize

640 x 480

800 x 600

1280 x 1024

1600 x 1200

Video I/O

Display Performance

NTSC: 560 line

PAL: 560 line

(depends on observation of the multi-burst pattern)

Input Signal

NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/

SECAM

480i, 480p, HDTV: 720p, 1080i

Interfaces

Computer/Component video: Mini D-sub 15 pin x 2

S-video: Mini DIN

Composite video: RCA

Monitor out

Serial: RS-232c

Composite audio RCA x 2

RJ-45

Audio Signal

500m Vrms/47K ohm

Security

Kensington®-style lock provision, anchor (metal)

bar for security lock or cable

Warranty

Two-year limited warranty, 90-day lamp warranty,

Epson Road Service Program and Epson

PrivateLine® dedicated toll-free support

(U.S. and Canada only)

Contents

Power cable, computer cable, projector remote

control, batteries, CD-ROM, Quick Setup Sheet,

PrivateLine support card, password protection

sticker

Accessory Part Numbers

Replacement remote	1456641
Presentation remote control	V12H007TOB
Universal ceiling mount	ELPMBUNI
Suspension adapter	ELPMBAPL
False ceiling plate	ELPMBFCP
Adjustable ceiling channel (ceiling plate not included or required)	ELPMBACC
Security bracket for security channel	ELPMBSEC
Distribution amplifier	ELPDA01
Component to VGA video cable	ELPKC19
S-video cable	ELPSV01
Samsonite® wheeled soft case	ELPKS35-S
Samsonite soft shoulder case for projector and laptop	ELPKS43
ATA molded hardshell case	ELPKS54
50" portable screen	ELPSC06
60" portable pop-up screen	ELPSC07
80" portable pop-up screen	ELPSC08
83.6" classroom style pull-down screen	ELPSC09
Duet™ screen	ELPSC80
Image Presentation Camera (ELPDC05)	V12H162020
Kensington security lock	ELPSL01

Support — The Epson ConnectionSM

Pre-sales Support

U.S. and Canada 800-463-7766

Automated Technical Support 800-922-8911

Internet Web Site www.epson.com

Presenters ONLINE presentersonline.com

* Lamp life results will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time.

Packaging Specifications

PowerLite 83c

Dimensions 16.8" x 14.9" x 7.2" (W x D x H)

Weight 11.0 lb

Replacement Lamp

Dimensions 6.3" x 5.5" x 5.6" (W x D x H)

Weight 0.7 lb

Master Carton

Dimensions 28.4" x 13.1" x 6.8" (W x D x H)

Weight 9.1 lb

Units Per Master Carton 10

Replacement Air Filter Set

Dimensions 3.9" x 1.2" x 4.9" (W x D x H)

Weight 0.88 lb

Master Carton

Dimensions 12.8" x 5.3" x 4.7" (W x D x H)

Weight 1.1 lb

Units Per Master Carton 10



Epson America, Inc.
3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.
3771 Victoria Park Avenue, Toronto, Ontario M1W 3Z5

www.epson.com
www.epson.ca

Specifications and terms are subject to change without notice. Epson is a registered trademark and Exceed Your Vision and E-TORL are trademarks of Seiko Epson Corporation. PowerLite and PrivateLine are registered trademarks, Duet is a trademark, and Epson Connection and Epson PresentersOnline are service marks of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2007 Epson America, Inc. CPD-23550R1 4/07 PDF